

Incorporating User Interaction into Imperative Languages

Keehang Kwon

Dept. of Computer Engineering, DongA University
Busan 604-714, Korea
khkwon@dau.ac.kr

Abstract: Adding versatile interactions to imperative programming – C, Java and Android – is an essential task. Unfortunately, existing languages provide little constructs for user interaction.

We propose a computability-logical approach [1] to user interaction. We illustrate our idea via C^{choo} , an extension of the core C with a new choice statement.

keywords: user interaction, choose, computability logic.

1 Introduction

Adding interactions to imperative programming has become an essential task. Despite the attention, imperative languages have traditionally lacked mechanisms for representing interactive values or interactive procedures. For example, a lottery ticket is in a superposition state of several possible values and require further interactions with the environment to determine their final value.

To represent interactive objects, we propose to adopt a choice-disjunctive operator in computability logic [1, 2]. To be specific, we allow a choice-disjunctive declaration statement of the form $choo(S, R)$ ($S \oplus R$ was originally used in [1].) where S, R are constant declarations or procedure declarations. This statement has the following semantics: request the user to choose one between S and R . For example, a lottery ticket, declared as $choo(value == \$0, value == \$1M)$, indicates that it has two possible values, nothing or one million dollars, and its final value will be determined by the the user.

On the other hand, the use of $choo$ in the main program requests the machine to choose one among several alternatives. This has the following execution semantics:

$$ex(\mathcal{P}, choo(G_1, \dots, G_n)) \leftarrow ex(\mathcal{P}, G_i)$$

where i is chosen by the machine and $\mathcal{P}$ is a set of procedure definitions. The notation $S \leftarrow R$ denotes reverse implication, *i.e.*, $R \rightarrow S$. In the

above definition, the machine chooses a successful G_i and then proceeds with executing G_i .

This paper focuses on the minimum core of C. This is to present the idea as concisely as possible. The remainder of this paper is structured as follows. We describe C^{choo} , an extension of core C with a new bounded-choice statement for the keyboard in Section 2. In Section 3, we present an example of C^{choo} . Section 4 concludes the paper.

2 The Language

The language is core C with procedure definitions. It is described by G -, C - and D -formulas given by the syntax rules below:

$$\begin{aligned} G &::= \top \mid A \mid cond \mid x = E \mid G; G \mid choo(cond_1; G_1, \dots, cond_n; G_n) \\ C &::= c == E \mid A = G \mid \forall x C \\ D &::= C \mid D \oplus D \end{aligned}$$

In the above, $\top$ represents a true (or continue) statement and $cond$ is a condition. Note that a condition is a legal statement in our language. $c == E$ declares that c is a constant with value E . A represents a head of an atomic procedure definition of the form $p(x_1, \dots, x_n)$ where $x_1, \dots, x_n$ are parameters. A C -formula is called a procedure definition. In the above, each $cond_i$ is assumed to be mutually exclusive in the $choo$ statement. This makes the execution quite deterministic. In the transition system to be considered, G -formulas will function as the main statement, and a set of D -formulas enhanced with the machine state (a set of variable-value bindings) will constitute a program. Thus, a program is a union of two disjoint sets, *i.e.*, $\{D_1, \dots, D_n\} \cup \theta$ where each D_i is a D -formula and θ represents the machine state. Note that θ is initially set to an empty set and will be updated dynamically during execution via the assignment statements.

We will present an interpreter which is adapted from [1, 2]. Note that this interpreter alternates between the execution phase and the backchaining phase. In the execution phase (denoted by $ex(\mathcal{P}, G, \mathcal{P}')$) it tries to execute a main statement G with respect to a program $\mathcal{P}$ and produce a new program $\mathcal{P}'$ by reducing G to simpler forms. If G becomes a procedure call, the interpreter switches to the backchaining mode. In the backchaining mode (denoted by $bc(D, \mathcal{P}, A, \mathcal{P}')$), the interpreter tries to solve a procedure call A and produce a new program $\mathcal{P}'$ by first reducing a procedure definition D in a program $\mathcal{P}$ to its instance (via rule (2)) and then backchaining on the

resulting definition (via rule (1)). To be specific, the rule (2) basically deals with argument passing: it eliminates the universal quantifier x in $\forall x D$ by picking a value t for x so that the resulting instantiation, written as $[t/x]D$, matches the procedure call A .

Below, we need some notation at the meta level.

- The notation S sand R denotes the sequential execution of two tasks. To be precise, it denotes the following: execute S and execute R sequentially. It is considered a success if both executions succeed.
- The notation S pand R denotes the parallel execution of two tasks. To be precise, it denotes the following: execute S and execute R in any order. Thus, the execution order is not important here. It is considered a success if both executions succeed.
- The notation S choose R denotes the selection between two tasks. To be precise, it denotes the following: the machine selects and executes one between S and R . It is considered a success if the selected one succeeds.

We need some definitions first. Understanding a formula $K \supset H$ as $\neg K \vee H$ and a procedure declaration $A = G$ as $G \supset A$, an *elementarization* of a formula F is obtained by

- replacing in F all the top occurrences of *choo* by $\perp$, and
- all the assignment statements by $\top$.

A formula is said to be *stable* if its elementarization is true.

As mentioned in Section 1, the notation $S \leftarrow R$ denotes reverse implication, *i.e.*, $R \rightarrow S$ at the meta level.

Definition 1. Let G be a main statement and let $\mathcal{P}$ be a program. Then the notion of executing $\langle \mathcal{P}, G \rangle$ successfully and producing a new program $\mathcal{P}' - ex(\mathcal{P}, G, \mathcal{P}')$ – is defined as follows:

- (1) $bc((A = G_1), \mathcal{P}, A, \mathcal{P}_1) \leftarrow ex(\mathcal{P}, G_1, \mathcal{P}_1)$. % A matching procedure for A is found.
- (2) $bc(\forall x D, \mathcal{P}, A, \mathcal{P}_1) \leftarrow bc([t/x]D, \mathcal{P}, A, \mathcal{P}_1)$. % argument passing
- (3) $ex(\mathcal{P}, A, \mathcal{P}_1) \leftarrow (D \in \mathcal{P} \text{ pand } bc(D, \mathcal{P}, A, \mathcal{P}_1))$. % a procedure call
- (4) $ex(\mathcal{P}, \top, \mathcal{P})$. % True is always a success.

- (5) $ex(\mathcal{P}, x = E, \mathcal{P} \uplus \{\langle x, E' \rangle\}) \leftarrow eval(\mathcal{P}, E, E')$. % the assignment statement. Here, $\uplus$ denotes a set union but $\langle x, V \rangle$ in $\mathcal{P}$ will be replaced by $\langle x, E' \rangle$.
- (6) $ex(\mathcal{P}, G_1; G_2, \mathcal{P}_2) \leftarrow (ex(\mathcal{P}, G_1, \mathcal{P}_1) \text{ seqand } ex(\mathcal{P}_1, G_2, \mathcal{P}_2))$. % sequential composition
- (7) $ex(\mathcal{P}, choo(c_1; G_1, \dots, c_n; G_n), \mathcal{P}_1) \leftarrow$
 choose(
 % if stable, the user makes a move first.
 $stable(\mathcal{P} \supset choo(c_1; G_1, \dots, c_n; G_n))$ sand
 $ex_u(\mathcal{P}, \mathcal{P}', I)$ sand
 % If user made some moves ($I=1$), then execution resumes.
 % Otherwise ($I=0$), it terminates with success.
 choose(
 $I = 1$ sand $ex(\mathcal{P}', choo(c_1; G_1, \dots, c_n; G_n), \mathcal{P}_1)$,
 $I = 0$),

 % if instable, the machine makes a move first.
 $\neg stable(\mathcal{P} \supset choo(c_1; G_1, \dots, c_n; G_n))$ sand
 choose k such that $cond_k$ pand $ex(\mathcal{P}, c_k; G_k, \mathcal{P}_1)$.

where $ex_u(\mathcal{P}, \mathcal{P}', I)$ is defined as follows:

Definition 2. Let $\mathcal{P}$ be a program of the form (D, θ) . Then the notion of the user executing (D, θ) and producing a new program $\mathcal{P}'$ of the form (D', θ) and a boolean value $I = ex_u(\mathcal{P}, \mathcal{P}', I)$ – is defined as follows:

- (1) $ex_u(C, C, 0)$.
- (2) $ex_u(D_0 \wedge D_1, D'_0 \wedge D'_1, I_0 \text{ or } I_1) \leftarrow ex_u(D_0, D'_0, I_0) \text{ pand } ex_u(D_1, D'_1, I_1)$
- (3) $ex_u(D_0 \oplus D_1, D, I) \leftarrow read(k) \text{ pand choose(}$
 $k = 0$ pand $D = D_0$ pand $I = 1$, % user chooses D_0 ,
 $k = 1$ and $D = D_1$ and $I = 1$) % user chooses D_1

Here, $I = 1/I = 0$ means that the user did make some/no move. Thus $\mathcal{P}'$ is obtained from $\mathcal{P}$ by the user executing *one choo* statement. The above definition easily extends to a set of D -formulas.

In the above, if $ex(\mathcal{P}, G, \mathcal{P}_1)$ has no derivation, then the machine returns the failure.

The rule (7) deals with choice statement. To execute $choo(c_1; G_1, \dots, c_n; G_n)$ successfully, the machine does the following:

- (1) It first checks whether the machine can perform the task correctly without doing anything (In other words, the current program is stable.).
- (2) If stable, the machine requests the user to make moves until the program becomes instable. Then the machine executes the *choo* statement.
- (3) If instable, the machine tries to find a true c_k and then execute G_k . Note that this step is deterministic due to the assumption that each c_i is mutually exclusive. If we allow nondeterminism here, then the execution model becomes quite complicated.

3 Examples

The following C-like code displays the amount of the tuition, based on the user's field of study.

```
major == medical % constant declaration
```

with the following G formula:

```
choo(
    major == english; tuition = $2,000,
    major == medical; tuition = $4,000,
    major == liberal; tuition = $2,200);
print(tuition);
```

This program expresses the task of the machine choosing one among three majors and printing its tuition.

Initially, this program is not stable. To make it stable, the machine must make a move by choosing $major == medical; tuition = \$4,000$. Finally, the system displays the amount of the tuition.

As a second example, our language makes it possible to customize the amount for tuition via interaction with the user.

```
print("type 1 for english,2 for medical,3 for liberal:");
choo(major == english, major == medical, major== liberal) % constant declarations
```

with the following G formula:

```
choo(
    major == english; tuition = $2,000,
    major== medical; tuition = $4,000,
    major== liberal; tuition = $2,200);
print(tuition);
```

Initially, note that this program is stable. Hence, the machine now requests the user to select one (by typing 1,2 or 3) among three majors. After it is selected – say 2 – the program becomes instable. Therefore, the machine must make a move by choosing $major == medical; tuition = \$4,000$. Then, the system displays the amount of the tuition.

4 Conclusion

In this paper, we extend the core Java with the addition of *choo* statements. This extension allows statements of the form $choo(S, R)$ where S, R are statements. These statements are particularly useful for representing interactive objects.

References

- [1] G. Japaridze, “Introduction to computability logic”, Annals of Pure and Applied Logic, vol.123, pp.1–99, 2003.
- [2] G. Japaridze, “Sequential operators in computability logic”, Information and Computation, vol.206, No.12, pp.1443-1475, 2008.
- [3] D. Miller, G. Nadathur, F. Pfenning, and A. Scedrov, “Uniform proofs as a foundation for logic programming,” Annals of Pure and Applied Logic, vol.51, pp.125–157, 1991.
- [4] Lynn Andrea Stein, “Interactive programming: revolutionizing introductory computer science,” ACM Comput. Surv. 28, 4es, Article No. 103, December 1996.

- [5] Roly Perera, “First-order interactive programming,” 12th international conference on Practical Aspects of Declarative Languages (PADL’10), Springer-Verlag, Berlin, Heidelberg, pp. 186-200, Jan. 2010.
- [6] Avinash C. Kak, Programming with Objects: A Comparative Presentation of Object-Oriented Programming with C++ and Java, John Wiley & Sons, Inc., New York, NY, USA, 2003.
- [7] Joseph Albahari, and Ben Albanhari, C# 5.0 Pocket Reference, O’Reilly Media, 224 pages, May 2012.
- [8] Joshua Bloch, Effective Java, Second Edition, Addison-Wesley, 346 pages, May 2008.